










### Intended use

Mipa Silikonentferner is a CHC-free cleaning and degreasing agent for all metallic and polymeric materials. It can be applied by paintbrush, brush, wipe, sponge or by spraying.

Spreading rate: --

### Processing instructions

	<b>Colour</b> colourless					
	<b>Mixing ratio</b>					
	<b>Hardener</b>		<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>		
	--	--	--	--		
	<b>Hardener</b>					
	<b>for complete paintwork</b>			<b>for partial paintwork</b>		
	--			--		
	<b>Pot life</b>					
	--					
	<b>Thinner</b>					
	--					
	<b>Spray viscosity</b>					
	<b>gravity spray gun</b>			<b>Airmix/Airless</b>		
	--			--		
	<b>Application mode</b>					
	<b>Application mode</b>	<b>Hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>Thinner</b>
	--	--	--	--	--	--
	<b>Flash-off time</b>					
	--					
	<b>Dry coat thickness</b>					
	--					
	<b>Drying time</b>					
	<b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	--	--	--	--	--	--

---

**Note**

- Storage:** at least 3 years in unopened original containers.
- VOC Regulation :** EU limit value for this product (category B/a): 850 g/l  
This product contains max. 743 g/l of VOC.
- Processing conditions:** from +10 °C and up to 80 % relative humidity. Ensure adequate air ventilation.
- Processing instructions:** –