

## :: Felgensilber

silver wheel spray

### CHARACTERISTICS

Silver Wheel Spray is a fast-drying acrylic-based spray to protect your wheels. This product protects your wheels from corrosion and will not rub or flake off. It will make your wheels look sparkling new again!

### APPLICATION

For use on all types and sizes of automotive wheels.

### PRODUCT DATA

Material data:

Color: Silver

Specific gravity: 0.711 g/mL

Solids by volume: 10 - 15%

Drying time (20°C): Approx. 15-20 minutes

Hardened in (20°C): 60 minutes

Coverage: 400 mL = 4-5 wheel rims

### HANDLING

Clean the wheels thoroughly, removing all rust, grease, and dirt. Shake the spray can well for at least 2 minutes before use. Spray on from approx. 25-30 cm away (10-12 in). Apply thin coats in steady, even up-and-down and side-to-side movements.

### PRECAUTIONS



11/2012

Contents under pressure. Do not store at temperatures above 50°C.

### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE