CAR SYSTEM®

11/2012

Plastic Cleaner

plastic degreaser antistatic

CHARACTERISTICS

- Antistatic effect for less dust embeddings
- Efficient removal of dirt, grease, oil, silicone, wax, tar, adhesive residues, etc.
- Easy and quick application
- Very time-saving application
- Efficient and reliable cleaning of all interior and exterior plastic car-parts

APPLICATION

- Spot repair
- New painting for all plastic car-parts

PRODUCT DATA

Specific weight: 0.79 g/cm^3
Shelf life: minimum 2 years
V.O.C.: < 790 g/l
Colour: transparent

HANDLING

SUBSTRATE:

- For all interior and exterior plastic car-parts

APPLICATION:

- 1-2 spray passes, if very dirty repeat process
- Wipe off with a clean, dry fleece

VOSSCHEMIE GMBH
Esinger Steinweg 50
D-25436 Uetersen

Telefon +49 (0) 4122/717 -0
Telefax +49 (0) 4122/717-158
E-Mail info@vosschemie.de

www.carsystem.org
www.vosschemie.de

a trademark of VOSSCHEMIE

• Allow cleaned substrate to dry completely

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Thin product contains isocyanate and can cause lung or breathing as well as hypersensitivity reaction. Before using or working with coatings material that contains isocyanate, all safety information's on the can label and the material safety data sheet must be read. Individuals with lung or breathing problems or prior reactions to isocyanate must not be exposed to vapour or spray mist.

The use of a respirator mask is necessary!

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Notice EU-safety data sheet as well as handling and warning notices on the label.

Copyright VOSSCHEMIE

VOSSCHEMIE GMBH
Esinger Steinweg 50
D-25436 Uetersen

Telefon +49 (0) 4122/717 -0
Telefax +49 (0) 4122/717-158
E-Mail info@vosschemie.de

www.carsystem.org
www.vosschemie.de