



Mipa Universal-Prefilled-Spray Lack-Spray Product Information

GB - 2/0317

Art.Nr.: 21200 0000

Mipa Universal Prefilled Spray is individually produced in quality and colour. By taking care of the specific application procedures of each product, high quality surface finishes equal to the product features will be achieved. The trader is liable for the final product!



Substrate:

Fully hardened and abraded old substrates
Thoroughly dry 1K-filler and 2K-filler materials



Cleansing: Pretreatment / Cleansing:

Pre-cleansing with Mipa Silikonentferner

Characteristics:

The paint is filled into the aerosol using an aerosol filling machine.
Equipped with an adjustable FAN-sprayhead.
Customised solutions for most areas of application.

**Colour /
Grade of Gloss:**

Depending on the specification of the product that has been filled

Preparation:



Filling quantity: 100 ml



Shake can vigorously until the mixing balls move freely!

Application:



Spray to test - Spraying distance approx. 20 - 30 cm
Depending on the final product

Flash-off:



Depending on the final product

After use:



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:



Drying:

Dust dry:

Depending on the final product

Set to touch:

Depending on the final product

Full hardness:

Depending on the final product

**Processing
Conditions:**

From +10°C and up to 80% relative air humidity

Storage:

In tightly closed original containers at least 2 years shelf life

**VOC-
Regulation:**

EC limiting value for the product (cat. B/e): 840 g/l (2007)

This product contains max. 840 g/l VOC [7.01 lbs/gal]

**Safety
Information:**

Read the corresponding Material Safety Data Sheet!

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.