

Mipa 2K-HS-Löser is a special solvent-based mixture for the dissolution of spray-dust on spot-repairs or blending work of 2K-HS coating systems.



Substrate:

Suitable for all all customary 2K-fillers, 2K-basecoats and 2K-clearcoats

Pretreatment / Cleansing:

Characteristics:

Excellent dissolution properties
Very good levelling qualities for blending work
Ideal for spot-repairs
Homogeneous surface finish
The transition zone can be easily polished to achieve a brilliant shine.

**Colour /
Grade of Gloss:**

Colourless

Preparation:



Shake can vigorously until the mixing balls move freely!

Application:



Apply directly onto the still wet film of paint in several thin layers in order to dissolve the transition zone and to obtain the best possible levelling qualities

Flash-off:



After use:



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:



Drying:

Dust dry:

Set to touch:

Buffing:

**Processing
Conditions:**

From +10°C and up to 80% relative air humidity

Storage:

In tightly closed original containers at least 2 years shelf life

**VOC-
Regulation:**

EU limiting value for the product (cat. B/e): 840 g/l (2007)

This product contains max. 800 g/l VOC [6.68 lbs/gal]

**Safety
Information:**

Read the corresponding Material Safety Data Sheet

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.