

Mipa 1K-Isolator-Spray is a fast drying special primer, which protects efficiently solvent-sensitive old paintworks (e.g. thermoplastic coatings, coatings based on alkyd resins, a.s.o.) from lifting or bleeding when overcoating with solvent-based coating systems.



Substrates:

old thermoplastic paintworks
coatings based on alkyd resins



Pre-treatment / Cleansing

pre-sand substrate thoroughly and clean with Mipa Silikonentferner

Characteristics:

fast drying
recoatable with Mipa 1K and 2K paints
very good insulating effect to protect from lifting or bleeding

Colour :
Gloss level

ochre yellow
matt

Preparation:



Shake can vigorously before use!

Application:



Spray to test - spray distance approx. 25 - 30 cm
apply 1 - 2 spray passes (= 15 - 25 µm)

Flash-off:



5 min between coats
1 h at 20°C before overcoating

After use:



After use hold the can upside-down and spray until the valve is empty in order to avoid that the paint dries up in the valve.

Drying times:



depend on the nature of the substrate:

Drying:

recoatable:

after approx. 1 h

Processing conditions:

from +10°C and up to 80% relative air humidity

Storage:

2 years if stored tightly closed in cool and dry places

VOC-regulations:

EU limit value for the product (cat. B/e): 840 g/l (2007)
This product contains max. 700 g/l of VOC.

Safety advice:

see material safety data sheet.

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.