

Mipa Felgensilber is a fast drying wheel rim paint based on a highly pigmented acrylic-quality. Excellent adhesion and resistance against chemical and mechanical strain. Specially suited to restore and to renew wheel rims, wheel trims or other parts.



### Substrate:

If necessary apply a priming coat Mipa Rapidprimer-Spray, in order to improve the adhesion and corrosive protection of the wheel rims.



### Pretreatment / Cleansing

Pre-cleansing with Mipa Silikonentferner or Mipa Kunststoffreiniger

### Characteristics

Fast drying  
High weather resistance  
Abrasion resistant  
Good surface hardness  
High opacity and coverage

**Colour /  
Grade of Gloss**

Brilliant silver  
Glossy

### **Preparation:**



Shake can vigorously until the mixing balls move freely!

### **Application:**



Spray to test - Spraying distance approx. 20 - 30 cm  
2 - 3 coats, dry film thickness 40 - 50 µm.

### **Flash-off:**



3 - 5 min. between each coating

### **After use:**



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

### **Drying Times:**



**Drying:**

**Dust dry:**

5 - 10 Min.

**Set to touch:**

20 - 30 Min.

**Full hardness:**

24 Stunden

### **Processing Conditions:**

From +10°C and up to 80% relative air humidity

### **Storage:**

In tightly closed original containers at least 2 years shelf life

### **VOC- Regulation:**

EC limiting value for the product (cat. B/e): 840 g/l (2007)  
This product contains max. 800 g/l VOC [ 6.68 lbs/gal]

### **Safety Information:**

Read the corresponding Material Safety Data Sheet

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.