








### Intended use

Solvent-free 2K EP hardener for solvent-free self-levelling Mipa 2K epoxy resin compounds.

### Processing instructions

	<b>Mixing ratio</b> hardener		<b>by weight (lacquer : hardener)</b>	<b>by volume (lacquer : hardener)</b>			
	See basic product		--	--			
	<b>Hardener</b>						
	--						
	<b>Pot life</b>						
	See basic product						
	<b>Thinner</b>						
	See basic product						
	<b>Spray viscosity</b>						
	See basic product						
	<b>gravity spray gun</b>			<b>Airmix/Airless</b>			
	--			--			
	<b>Application mode</b>						
	<b>application mode</b>	<b>hardener</b>	<b>pressure (bar)</b>	<b>nozzle (mm)</b>	<b>spray passes</b>	<b>dilution</b>	
	See basic product	--	--	--	--	--	
	<b>Drying time</b>						
	<b>hardener</b>	<b>object temperature</b>	<b>dust dry</b>	<b>set to touch</b>	<b>ready for assembly</b>	<b>sandable</b>	<b>recoatable</b>
	See basic product	--	--	--	--	--	--

### Note

<b>Characteristics:</b>	binder base:	polyamine adduct
	solids content (% by weight):	100
	solids content (% by volume):	--
	delivery viscosity DIN 53211 4 mm (in s):	thixotropic
	density DIN EN ISO 2811 (kg/l):	1,0 - 1,1
	gloss level ISO 2813 at 60° (GU):	See basic product

**Properties:** See basic product

**Theoretical spreading rate :** See basic product

<b>Storage:</b>	for at least 2 years in the unopened original container. Optimum storage conditions between + 5 °C and + 25 °C, avoid direct sunlight. Other storage conditions may lead to undesirable properties of the material.
<b>VOC Regulation :</b>	See basic product
<b>Processing conditions:</b>	See basic product
<b>Substrate preparation:</b>	See basic product
<b>Proposed coating structure:</b>	See basic product
<b>Special notes:</b>	For professional use only.
<b>Cleaning of tools:</b>	Clean tools immediately after use with Mipa EP-Verdünnung.