

Product Information

Effective organic solvent mix to dilute the Mipa BC paints. For further information concerning typical or optimum levels of use and for more precise details, please consult our Product Informations for the base products.

Colour shade	colourless			
Mixing ratio				
Hardener				
Thinners				
Spraying viscosity 20° C				
Application	spraying pressure	spraying nozzle	spraying operations	
Air / Flowjar - Spray gun				
Airless / Airmix				
Pot life				
Coat thickness / dry film				
Curing time / Flash off time				
Dry	recoat time	dust dry	set to touch	full hardness
Object Temp. 20° C				
Object Temp. 60° C				

Safety instructions :

Keep containers tightly closed. Keep away from heat and flame, fire heat or other potential sources of ignition. The preparation may charge electrostatically. Always use earthing leads when taking out or transferring from one container to another.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.